

WD4190



WASHER DISINFECTOR WITH DRYING SYSTEM, EN15883 APPROVED
BASIC LINE - WASHER DISINFECTOR 90 CM WITH DRYING SYSTEM
[Download PDF](#)

- ✓ washing up to 95 °C - antibacterial thermal disinfection
- ✓ programs: 9 default + 6 custom
- ✓ microprocessor programmable electronic control
- ✓ serial port RS232 for connection to external printer or PC
- ✓ forced hot air drying system with HEPA air filter
- ✓ high efficiency steam condenser Ecoslim, with cold water injection
- ✓ peristaltic pump for liquid detergent and level sensor
- ✓ peristaltic pump for acid liquid neutralizer and level sensor
- ✓ possibility of installing 1 additional peristaltic pump
- ✓ washing chamber and internal door in stainless steel AISI 316L
- ✓ external panels in stainless steel AISI 304
- ✓ detergent cabinet made of AISI 304 stainless steel 4 x 5 liters tanks
- ✓ external dimensions LxDxH: 900 x 600 x 850 mm
- ✓ internal working dimensions LxDxH: 525 x 490 x 570 mm
- ✓ incorporated water softener with salt sensor
- ✓ cold water and demineralized water connections
- ✓ electronic door lock system for user safety
- ✓ electrical connection: 3/N/PE 400 V - 50 Hz - 7 kW max
- ✓ single-phase version available: 1/N/PE 230 V - 50 Hz - 3,3 kW max (cod. WD4190-1)
- ✓ three-phase without neutral version available: 3/PE 230 V - 50 Hz - 7 kW max (cod. WD4190-3)
- ✓ 60 Hz version available
- ✓ without trolleys
- ✓ n. 2 independent washing levels through telescopic guides available (cod. WD4190R)

Smeg S.p.A. Via Leonardo Da Vinci, 4 - 42016 Guastalla (RE) Italy - P. IVA 01555030350
Phone +39 0522 8211 - fax +39 0522 821453 - service.instruments@smeg.it

