




HYC-68A







Audible buzzer and visible flashing light



Five Alarm **Functions**

High/low temperature, power failure, door ajar, sensor error, low battery



Air Cooling, **Auto Defrost**

Better cabinet temperature uniformity, auto defrost

Ergonomic Design



Temperature Control





Lockable Design

Specifications HYC-68A

Technical Data

Cabinet Type	Upright, glass door
Climate Class	N
Cooling Type	Forced air cooling
Defrost Mode	Auto
Refrigerant	CFC-Free
Noise((dB(A))	35

Performance

Town Dange (C)	2.0	
Temp Range(℃)	2~8	



Control

Controller	Microprocessor
Display	LED

Electrical Data

Power Supply(V/Hz)	220-240/50	115/60
Power(W)	84	68
Electrical Current(A)	0.65	1.1

Dimensions

Capacity(L/Cu.Ft)	68/2.4
Net/Gross Weight(approx)	38/40(kg) 83.8/88.2(lbs)
Interior Dimensions(W*D*H)	415*385*505(mm) 16.3*15.2*19.9(in)
Exterior Dimensions(W*D*H)	495*580*660(mm) 19.5*22.8*26.0(in)
Packing Dimensions(W*D*H)	540*640*710(mm) 21.3*25.2*28.0(in)
Container Load(20'/40'/40'H)	108/228/228

Functions

High/Low Temp	Υ	
Power Failure	Υ	
Sensor Error	Υ	
Low Battery	Υ	
Door Ajar	Y	
Remote System	Υ	

Accessories

Foot	Υ
Shelves /Basket	2/1

Others

Certificate	CE,UL	

Hajer Biomedical UK

Address:2 Birch House, Brambleside, Bellbrook Industrial Estate, Uckfield, East Sussex, TN22 1QQ,United Kingdom TEL:+44(0) 1825 744 696(Head Office) www.haierbiomedical.co.uk







Note: If slight difference occurs between pictures







and actual products, please refer to actual products. Our company reserves the right of final interpretation to this brochure and please contact with us for further information you might need.